

BURSTPROOF™ REGULAR STEAM (THERMOCURE)

This hose is designed for saturated steam service up to +406°F and super-heated steam service up to +450°F where petroleum products will not contact the hose. This hose meets MIL H 28596B, Type 1, Grade A specifications. Available in black or red, this hose's EPDM cover is reinforced with two braids of carbon steel wire providing flexibility and abrasion resistance. This durable hose provides a constant working pressure of 250 psi and is available in a range of sizes.



RESISTANCE  
BRANDING Thermoid HBD Industries
 BP Steam Hose Made In USA

Cover Color: Black or Red
Oil Resistance: Limited
Construction:
Tube: EPDM
Cover: EPDM
Reinforcement: Two braids of carbon steel wire
Temperature Range: For saturated steam service to +406°F (+208°C)
 Super-heated steam to +450°F (+232°C)
Packaging: Reels – 1/2"-1" I.D. or 50 ft. lengths
 1-1/4" - 2" I.D. – 50 ft. lengths

Product Number	Nominal I.D.		Nominal O.D.		Reinforcement Braids	Working Pressure		Min. Bend Radius		Weight	
	(inches)	(mm)	(inches)	(mm)		(psi)	(Mpa)	(inches)	(mm)	(lb/ft)	(Kg/m)
Black											
22052321662	1/2	12.70	1.00	25.40	2	250	1.72	3.00	76.20	0.38	0.57
22052481662	3/4	19.05	1.28	32.54	2	250	1.72	4.50	114.30	0.52	0.77
22052641662	1	25.40	1.53	38.89	2	250	1.72	7.00	177.80	0.77	1.15
01104413502	1-1/4	31.75	1.88	47.63	2	250	1.72	8.75	222.25	1.10	1.64
01104414502	1-1/2	38.10	2.11	53.58	2	250	1.72	10.50	266.70	1.23	1.83
01104415502	2	50.80	2.66	67.47	2	250	1.72	14.00	355.60	1.62	2.41
Red											
22052322662	1/2	12.70	1.00	25.40	2	250	1.72	3.00	76.20	0.38	0.57
22052482662	3/4	19.05	1.28	32.54	2	250	1.72	4.50	114.30	0.52	0.77
22052642662▲	1	25.40	1.53	38.89	2	250	1.72	7.00	177.80	0.77	1.15

▲ = Make To Order (MTO)